



### **BALDER MAX**

---

Waterproof 80mm diameter LED tubular for general and technical lighting. Balder MAX is a range of Professional LED tubes with high luminous intensity made of polycarbonate and stainless steel for maximum resistance.

#### APPLICATION

- General lighting
- Lighting technical areas
- Car park lighting

# TUBE BALDER MAX

Technical characteristics	Baldrmax33	Baldrmax66	Baldrmax99	Baldrmax132
Dimensions	380mm	650mm	1000mm	1250mm
Number of LEDs	33	66	99	132
Power	17W	33W	49W	65W
Luminous flux clear tube	2000lm	4000lm	6000lm	8000lm
Luminous flux diffusing tube	1200lm	2400lm	3600lm	4800lm
Diameter	80mm			
Materials	Polycarbonate and stainless steel in option			
Color temperature	3000K   4000K   5000K			
Angle	30°   60°   90°   120°			
Life span	50 000 hours L 70			
operating temperature	-20° to +40°C			
IRC	Optional > 80 et > 90			
Optional detector	Integrated HF 160° adjustable			
Voltage	220Vca 50hertz			
Optional dimming	DALI   DMX   0-10 V			
Electrical class	Class II			
Connection	Standard cable or optional CR1-C1			
IK	IK10			
IP	IP67			
Fixation	2 stainless steel mounting brackets			
Types of Fixations	Standard   Mono point   Suspended			
Compliance	RoHS   CE   NF-EN 60598			
Glow wire test	850°C			
Warranty	3 years			
Place of manufacture	France			

Photometric data +/- 10%, the manufacturer reserves the right to modify the characteristics without prior notice.