



LUMI RAMP C COLOR | H24W26

LED STRIP Lumi'Ramp C H24W26 equipped with Lumi Color (Colour LED) in an anodised aluminium profile with polyurethane waterproof encapsulation. Thanks to its tailor-made dimensions, this ruler can be used for all your indoor and outdoor projects.

APPLICATION

- Architectural lighting
- Interior Lighting
- Outdoor lighting

LUMI RAMP C COLOR | H24W26

Technical data	H24W26 12W	H24W26 8W
Dimensions	Section 12*16mm - Length 3m max.	
Number of LEDs	60LED/m	120LED/m
Power	12W	8W
Materials	Anodised aluminium profile with clear or diffusing PC cover. Anti-UV PU resin.	
Colors	Red Green Blue Amber	
IRC	80	
Luminous flux	50lm (red) 80lm (green) 20lm (blue) 30lm (amber)	50lm (red) 80lm (green) 20lm (blue) 30lm (amber)
Gradable	Yes	
Angle	120°	
Lifespan	50 000 hours L 70	
operating temperature	-20°C to +50°C	
Voltage	24Vcc	
Electrical class	Class III	
Connection	Cable HO5 RNF 2/4 wires*0,75mm ² 1 meter long	
IK	IK10	
IP	IP67	
Fixation	By stainless steel or composite clips	
Glow wire test	850°C	
Warranty	3 years	

Photometric data +/- 10%, the manufacturer reserves the right to modify the characteristics without prior notice.

