



MINI BALDER

Waterproof 50mm diameter LED tube for general and technical lighting. Mini Balder is a range of tubular luminaires with high luminous intensity made of polycarbonate and stainless steel for maximum resistance.

APPLICATION

- General lighting
- Lighting technical areas
- Car park lighting

Technical characteristics	MiniBalder24	MiniBalder48	MiniBalder72	MiniBalder96
Dimensions	380mm	650mm	1000mm	1250mm
Number of LEDs	24	48	72	96
Power	8W	16W	24W	32W
Luminous flux clear tube	1000lm	2000lm	3000lm	4000lm
Luminous flux diffusing tube	600lm	1200lm	1800lm	2400lm
Diameter	50mm			
Materials	Polycarbonate and stainless steel in option			
t° de couleur	3000K 4000K 5000K			
Angle	30° 60° 90° 120°			
Life span	50 000 hours L 70			
operating temperature	-20° to +40°C			
IRC	Optional > 80 et > 90			
Optional detector	Integrated HF 160° adjustable			
Voltage	220Vca 50hertz			
Optional dimming	DALI DMX 0-10 V			
Electrical class	Class II			
Connection	Standard cable or optional CR1-C1			
IK	IK10			
IP	IP67			
Fixation	2 stainless steel mounting brackets			
Types of Fixations	Standard Mono point Suspended			
Compliance	RoHS CE NF-EN 60598			
Glow wire test	850°C			
Warranty	3 years			
Place of manufacture	France			

Photometric data +/- 10%, the manufacturer reserves the right to modify the characteristics without prior notice.